



Primer 150 is a universal primer based for porous surfaces. Suitable for Silicone sealants, Hybrids and SMX Polymer sealants. To be used in situation where capillary pressure exists. can be used on all porous surfaces, joint sides of expansion joints and joint sides of porous materials with raised water pressure.

Features & Benefits

- Blocks capillaries in substrate
- Improves adhesion
- Can be covered after 1hr
- Fast hand tight bond.

Applications

- All porous surfaces.
- Joint sides of expansion joints.
- Joint sides of porous materials with raised water pressure.

Technical data

Basis	Synthetic resins
Consistency	Fluid
Curing system	Physical drying and reaction with moisture
Density	Ca. 0,93 g/ml
Flashpoint	8 °C
Drying time (23°C and 50% R.H.)	Approx. 60 min (20°C/ 65% R.H.)
Consumption (*)	Ca. 5 m ² /L
Application temperature	5 °C → 25 °C

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.



Product description

Primer 150 is a universal primer for porous substrates.

Properties

- Liquid, easy application
- Suited for silicones and Hybrid (MS) sealants

Applications

- All porous surfaces.
- Joint sides of expansion joints.
- Joint sides of porous materials with raised water pressure.

Shelf life

12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Substrates

Substrates: all common porous building substrates
Nature: rigid, clean, dry, free of dust and grease.

Application method

Recommendation : after application minimum 1 and maximum 4 hours of waiting time before applying any joint sealant.

Application method: Apply with brush or roller in one full covering layer.

Cleaning: With White spirit immediately after use (not cured).